

TOOLS AVAILABLE

The Invicta can be equipped with all tools compatible with the following tool holders:

- Multifunctional **Tool Holder**
- Versa-Tool Holder
- Fixed Tool Holder









TECHNICAL DATA

				NEW		
Invicta Models	V0806	V0812	V1015	V1612		
Cutting Size	812 x 610 mm (32" x 24")	812 x 1219 mm (32" x 48")	1016 x 1524 mm (40" x 60")	1550 x 1220 (61" x 48")		
Width	1450 mm (57")	1920 mm (75.5")	2080 mm (81.9")	2110 mm (83")		
Depth	1390 mm (54.7")	1390 mm (54.7")	1590 mm (62.6")	1920 mm (75.6")		
Height	1250 mm (49.2")	1250 mm (49.2")	1250 mm (49.2")	1250 mm (49.2")		
Weight	172 kg (379.1 lbs)	228 kg (502.65 lbs)	265 kg (584.2 lbs)	329 kg (725 lbs)		
Max Cutting Speed	Up to 400 mm/s (16 "/sec)	Up to 400 mm/s (16 "/sec)	Up to 400 mm/s (16 "/sec)	Up to 910 mm/s (26.3 "/sec)		
Acceleration	Up to 0.5 m/sec ² (19.7"/sec ²)	Up to 0.5 m/sec ² (19.7"/sec ²)	Up to 0.5 m/sec ² (19.7"/sec ²)	Up to 2 m/sec² (78.7"/ sec²)		
Power Requirements	Single Phase - 230V 50Hz 9.6A - 2,2 KVA Single Phase - 208/230V 60Hz 12A - 2,5 KVA					
Air Requirements	6 bar (3,5 CFM) 8 bar (5,3 CFM) with Oscillating Tool					
File Format	SVG, .PLT, .DXF, .CF2, .HPGL, .XML, .PDF					
Tool Change	Manual					
Tools Available		90°, 45°, 40°, Embossing, Creasing, Drawing, Oscillating Tool and Kiss Cut tool				
Tool Holders	1 + 1F					
Connectivity	Ethernet or USB					



Magnet sheet

Marie Acquires prog hat the companies of the Astronomic they gast collaborar collators to statingfun 2000 also 10.00
Topo la corringità Softwa e Esgagnian Vi apportune per Parlaggian regione pensso l'Agritunisme Rhang

Folding carton

Height	1250 mm (49.2")	1250 mm (49.2")	1250 mm (49.2")	1250 mm (49.2")			
Weight	172 kg (379.1 lbs)	228 kg (502.65 lbs)	265 kg (584.2 lbs)	329 kg (725 lbs)			
Max Cutting Speed	Up to 400 mm/s (16 "/sec)	Up to 400 mm/s (16 "/sec)	Up to 400 mm/s (16 "/sec)	Up to 910 mm/s (26.3 "/sec			
Acceleration	Up to 0.5 m/sec ² (19.7"/sec ²)	Up to 0.5 m/sec ² (19.7"/sec ²)	Up to 0.5 m/sec ² (19.7"/sec ²)	Up to 2 m/sec² (78.7"/ sec²			
Power Requirements	Single Phase - 230V 50Hz 9.6A - 2,2 KVA Single Phase - 208/230V 60Hz 12A - 2,5 KVA						
Air Requirements	6 bar (3,5 CFM) 8 bar (5,3 CFM) with Oscillating Tool						
File Format	SVG, .PLT, .DXF, .CF2, .HPGL, .XML, .PDF						
Tool Change	Manual						
Tools Available	90°, 45°, 40°, Embossing, Creasing, Drawing, Oscillating Tool and Kiss Cut tool						
Tool Holders	1 + 1F						
Connectivity	Ethernet or USB						
Data Buffer	External PC*						
Media Holding System	Vacuum Bed and Pneumatic Clamping System						
Fixed Tool	Pen (Optional)						
Cutting Capacity	0.1 > 5 mm (0.20") with Tangential Cutting Tool 0.1 < 20 mm (0.79") with Oscillating Tool						
Repeatability	≤0.1 mm						
Supported OS	Windows 7, 10, 11						
CropMarks Rec.	Camera (Included) + Software (Optional)						